. References

[1] A. Ghadimi, R. Saidur, H.S.C. Metselaar, 2011, “A review of nanofluid stability properties and characterization in stationary conditions”, International Journal of Heat and Mass Transfer, Vol. 54,pp. 4051–4068.

[2] A. Berthold, F. Haucke, 2017, “Experimental Investigation of Dynamically Forced Impingement Cooling” Proceedings of ASME Turbo Expo 2017: Turbomachinery Technical Conference and Exposition, GT2017, USA.

[3] Abraham, F. F., 2000, “Dynamically Spanning the Length Scales from theQuantum to the Continuum,” Int. J. Mod. Phys. C, Vol. 11(6), pp. 1135–1148.

[4] Adewumi O.O., Bello-Ochende T., Meyer J.P., 2014, “GeometricOptimisation of multi-layered microchannel heat sink with different flow arrangements”, Proceedings of the 15th International Heat Transfer Conference, IHTC-15, Kyoto, Japan. Paper no. IHTC15-9148.

[5] Chiriac, V.A., Ortega, A., 2002. “A numerical study of the unsteadyflow and heat transfer in a transitional confined slot jet impingingon an isothermal surface”, Int. J. Heat Mass Transfer, Vol. 45, pp. 1237–1248.

[6] E.V. Timofeeva, J. L. Routbort, D. Singh, 2009, “Particle shape effect on thermophysical properties of alumina nanofluids”, Journal of Appl. Physics, Vol. 106, pp. 0143304-15.

[7] F. Haucke, W. Nitsche, D. Pieter, 2016, “Enhanced Convective Heat Transfer Due to Dynamically Forced Impingement Jet Arrays”, Proceedings of ASME Turbo Expo 2016: Turbomachinery Technical Conference and Exposition, GT2016, South Korea.

[8] Ganesh Ranakoti, Irtisha, Sandhya Dewangan, Siddharth Koshti, Roshan Nemade, 2012, “Heat Transfer Enhancement by Nano Fluids”, ME642-Convective Heat and Mass transfer.

[9] Han Shen, Yingchun Zhang, Hongbin Yan, 2017 “Convective Heat Transfer of Parallel-Flow and Counter-Flow Double-Layer Microchannel Heat Sinks in Staggered Arrangement”

Proceedings of the ASME 2017 International Mechanical Engineering Congress and Exposition, IMECE2017, USA.

[10] He, Y., Jin, Y., Chen, H., Ding, Y., Chang, D., and Lu, H., 2007, "Heat Transfer and Flow Behaviour of Aqueous Suspensions of TiO_2 Nanoparticles Flowing Upward Through a Vertical Pipe," Int. J. Heat Mass Transfer, Vol. 50, pp. 2272–2281.

[11] J. Garg et al., 2008, "Enhanced thermal conductivity and viscosity of copper nanoparticles in ethylene glycol nanofluid", Journal of Applied Physics, Vol. 103, pp. 074301-11.

[12] Kalteh M., Kouhikamali R., Akbari S., 2016, "Numerical simulation of nanofluid heat transfer in a double-layered microchannel heat sink using two phase mixture model", Journal of Nanotechnology, Vol. 5, pp. 139-147.

[13] Kinloch, I. K., Roberts, S. A., and Windle, A. H., 2002, "A Theological Study of Concentrated Aqueous Nanotube Dispersions," Polymer, Vol. 43, pp. 7483–7491.

[14] L. Syam Sundar, E. Venkata Ramana, Manoj K. Singh, Antonio C.M. Sousa, 2014, "Thermal conductivity and viscosity of stabilized ethylene glycol and water mixture Al_2O_3 nanofluids for heat transfer applications: An experimental study", International Communications in Heat and Mass Transfer, Vol. 56, pp.86–95.

[15] Lee, S. P., and Choi, U. S., 1999, "Application of Metallic Nanoparticle Suspensions in Advanced Cooling Systems," Recent Advances in Solids/Structures and Application of Metallic Materials, Vol. 342, Y. Kwon, D. Davis, and H. Chung, eds., ASME, New York, pp. 227–234.

[16] Liu, J., Chen, S. Y., Nie, X. B., and Robbins, M. O., 2007, "A Continuum–Atomistic Simulation of Heat Transfer in Micro- and Nano-Flows," J. Comput. Phys., Vol. 227(1), pp. 279–291.

[17] Li, X., Gaddis, J.L., Wang, W., 2001, “Mist/steam heat transfer in confined slot jet impingement”, ASME J. Turbomachinery. Vol. 123, 161–167.

[18] M. Keenan, R. S. Amano, S. Ou, 2013, “Study of An Impingement Cooling Jet Array for Turbine Blade Cooling with Single and Double Exit Cases, Proceedings of ASME Turbo Expo 2013: Turbine Technical Conference and Exposition, GT2013, USA.

[19] Mahajan R., Nair R., Wakharkar V., 2002, “Emerging directions for packaging technologies”, Intel Technology Journal, Vol. 6, pp. 104-112.

[20] Nie, Q., and Joshi, Y., 2008, “Multiscale Thermal Modeling Methodology for Thermoelectrically Cooled Electronic Cabinets,” Numer. Heat Transfer, Part A, Vol. 53(3), pp. 225–248.

[21] P. Naphon, S. Wongwises, 2010, “Investigation on the jet liquid impingement heat transfer for the central processing unit of personal computers”, Int. Commun. Heat Mass Transfer, Vol. 37, pp. 822–826.

[22] P. Naphon, S. Klangchart, 2011, “Effects of outlet port positions on the jet impingement heat transfer characteristics in the mini-fin heat sink”, Int. Commun. Heat Mass Transfer, Vol. 38, pp.1400–1405.

[23] Patrice Estellé, Salma Halelfadl, Thierry Maré, 2015, “Thermal conductivity of CNT water based nanofluids: experimental trends and models overview”, Journal of Thermal Engineering, Yildiz Technical University Press, Istanbul, Turkey, Vol. 1, Issue No. 2, pp. 381-390.

[24] Paritosh Garg, Jorge L. Alvarado, Charles Marsh, Thomas A. Carlson, David A. Kessler, Kalyan Annamalai, 2009, “An experimental study on the effect of ultrasonication on viscosity and heat transfer performance of multi-wall carbon nanotube-based aqueous nanofluids”, International Journal of Heat and Mass Transfer, Vol. 52, pp.5090–5101.

[25] R. Prasher, D. Song. J. Wang. P. Phelan, 2006, “Measurements of nanofluid viscosity and its implementations for thermal applications”, App. Phys. Lett. Vol. 89, pp. 502-14.

[26] R. Bunker, 2008, “Innovative Gas Turbine Cooling Techniques”, in Thermal Engineering in Power Systems, Southampton, WIT Press.

[27] Rezania A., Rosendahl L.A., Andreasen S.J., 2012, “Experimental investigation of thermoelectric power generation versus coolant pumping power in a miocrochannel heat sink”, International Communications Heat Mass Transfer, Vol. 39, pp. 1054-1058.

[28] Sadhana Bhusal, Long Phan and Cheng-Xian Lin, 2017, “Surface Geometry Optimization for Convection Flow over Super Hydrophobic Surfaces” Proceedings of the ASME 2017 Heat Transfer Summer Conference, HT2017,USA.

[29] Sarit K. Das, Stephen U. S. Choi, Wenhua Yu and T. Pradeep, 2010, “Nanofluids Science and Technology”, A John Wiley & Sons, publication.

[30] T. R. Krishna, S. G. Moulic, A. Bhattachyarya, 2017 “Experimental Study on Buoyancy-Induced Convection in Open Cell Aluminium Metal Foam” Proceedings of the ASME 2017 International Mechanical Engineering Congress and Exposition, IMECE2017, USA.

[31] V.I. Terekhov, S.V. Kalinina, V.V. Lemanov, 2010,“The mechanism of heat transfer innanofluids: state of the art (review). Part 1”. Synthesis and properties ofnanofluids, Thermophys. Aeromechanics, Vol. 17 (1). Pp. 1–14.

[32] V. Kumaresan a, R. Velraj a, Sarit K. Das, 2012, “Convective heat transfer characteristics of secondary refrigerant based CNT nanofluids in a tubular heat exchanger”, International journal of refrigeration, Vol. 35, pp. 2287-2296.

[33] W. Arshad, H.M. Ali, 2017, “Experimental investigation of heat transfer and pressuredrop in a straight minichannel heat sink using TiO2 nanofluid”, Int. J. Heat MassTransfer, Vol. 110, pp. 248–256.

[34] Wang X.D., Huang Y.X., Cheng C.H., Jang J.Y., Lee D.J.,Yan W.M., Su A., 2010, “An inverse geometry design problem foroptimization of single serpentine flow field of PEM fuel cell”, International Journal of Hydrogen Energy, Vol.35, pp. 4247-4257.

[35] Xuan Wang, Le-Ping Zhou, Xiao-Feng Peng,2003, “A fractal model for predicting the effective thermal conductivity of liquid with suspension of nanoparticles”, International Journal of Heat and Mass Transfer, Vol. 46, pp. 2665–2672.

[36] Y. Xuan, Roetzel, 2009, “Conceptions of heat transfer correlation of nanofluids”, Int. Journal of Heat Mass Transfer, Vol. 43, pp. 3701–3707.